


Declaration of performance

No. HHDE 8 0901

Unique identification code of the product-type		H + H Blokfix	
Intended use	Designed thin layer masonry mortar (T) applied in thin layers for internal and external applications		
Manufacturer:	LIP Bygningsartikler A/S, Industrivej 16, 5580 Nr. Åby, Danmark		
System of AVCP:	2+		
Harmonized standard:	EN 998-2:2016		
Notified body	NB 1073		
Declared performance			
Compressive strength	NPD		
Bond strength, on aircrete density 375	$\geq 0,3 \text{ N/mm}^2$		
Bond strength, on aircrete density 535	$\geq 0,4 \text{ N/mm}^2$		
Flexural strength, on aircrete density 375, f _{xk1}	0,35 MPa		
Flexural strength, on aircrete density 375, f _{xk2}	0,20 MPa		
Flexural strength, on aircrete density 535, f _{xk1}	0,50 MPa		
Flexural strength, on aircrete density 535, f _{xk2}	0,45 MPa		
Reaction to fire	Class A1		
Contents of chlorides	NPD		
Water absorption	NPD		
Water vapour permeability	NPD		
Thermal conductivity/Density	NPD		
Durability	NPD		
Dangerous substances	NPD		
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.			
Signed for and on behalf of the manufacturer by:			
Name	Kristian K. Mortensen	Date	25-08-2017
Signature		Place	Nr. Åby