452316-ANGLEBRACKET 90x60x60x2.5 CE

ESSVE Angle brackets are intended to be used for anchoring crossing frameworks, as well as between wooden posts and awls or hammer bands.

ESSVE Angle fittings are made of 2.0, 2.5 or 3.0 mm hot-dip galvanised sheet steel. The angle brackets are equipped with 5.0 mm holes and larger bolt holes. The angle fittings are manufactured in two versions, with (MF) or without reinforcement.




Dimensions [mm]				Hole flange A Hole flange	
а	b	С	d	Anchor nail	Anchor nail
90	60	60	2.5	8	5


Characteristic resistance									
Assembly /mountin g	F _{Rk,1} [kN] Pillar	F _{Rk,1} [kN] Beam	F _{Rk,2/3} [kN]	F _{Rk,4} [kN]	F _{Rk,5} [kN]				
Simple	Simple 1.4 1		3.0	-	-				
Double	2.8	1.4	6.0	6.9	6.9				
Allowable load [kg]									
Simple	60	60	130	-	-				
Double	125	60	265						

 Values refer to fittings as a system with ESSVE 4.0x60 anchor nails in accordance with ETA-23/0236

- Single angle brackets must be mounted on the underside of the beam
- When horizontal and vertical transverse force act
- $\left(\frac{F_{1,d}}{F_{Rd,1}}\right)^2 + \left(\frac{F_{2,d}}{F_{Rd,2}}\right)^2 + \left(\frac{F_{3,d}}{F_{Rd,3}}\right)^2 + \left(\frac{F_{4,d}}{F_{Rd,4}}\right)^2 + \left(\frac{F_{5,d}}{F_{Rd,5}}\right)^2 \le 1,0 \text{ simultaneously, the condition shall be fulfilled}$
- The allowable load is shown in unit [kg] and can be applied directly. All safety factors according to Eurocode 5 are already included with partial coefficient (_YM = 1.3), load duration and moisture factor (kmod = 0.8) as well as assumed load factor for ultimate limit state (_Y load = 1.4) according to EN 1990




FLANGE A



FLANGE B



PILLAR



BEAM



Essve Produkter AB Tel 08–623 61 50 www.essve.se info@essve.se

