



## DECLARATION OF PERFORMANCE

DK001/DoP20130107

1. Dry-pressed ceramic tiles with high water absorption E>10%,  
Group BIII, normative (Annex) K, glazed (GL)
2. Dry-pressed ceramic tiles with high water absorption E>10%,  
Tile size (mm):197x197x7; 200x200x7; 200x250x7; 250x330x7,5; 200x400x8,5; 250x400x8,5; 200x500x9;  
330x500x9; 200x600x9,5; 300x600x10
3. Intended use:  
Ceramic tiles, dry-pressed for internal walls
4. Name and contact information of manufacturer  
Hitit Seramik San. Tic. A.Ş.  
Organize Sanayi Bölgesi  
PK:43 64100  
UŞAK  
TÜRKİYE
6. System of assessment and verification of constancy of performance AVCP 4.
7. FPC according AVCP class 4.
9. Relevant clauses

| Essential characteristics                                 |  | Performance                                                                                         | Harmonized technical specification |
|-----------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------|------------------------------------|
| Reaction to fire                                          |  | A1FL<br>(CWT)                                                                                       | EN 14411:2012                      |
| Release of dangerous substances for:<br>-Cadmium<br>-Lead |  | TS EN ISO 10545-4<br>NPD<br>NPD                                                                     |                                    |
| Modulus of rupture                                        |  | thickness <7,5 mm:12N/mm <sup>2</sup><br>thickness ≥7,5 mm:15N/mm <sup>2</sup><br>TS EN ISO 10545-4 |                                    |
| Thermal shock resistance                                  |  | Pass<br>TS EN ISO 10545-9                                                                           |                                    |
| Bond strength                                             |  | >05N/mm <sup>2</sup><br>Cementitious adhesive<br>Type C2 /EN12004                                   |                                    |
| Durability                                                |  | Pass                                                                                                |                                    |

10. Behalf of manufacturer signed: Özkan PEKER, R&D Manager

UŞAK

21.06.2013