

## **DECLARATION OF PERFORMANCE**

## 003 CPR 15.06.2013

1-THE PRODUCT TYPE	Dry-pressed ceramic WALL TILES, with water absorption Eb>10%,	
2- INTENDED USE(S)	For internal walls	
3- NAME AND CONTACT ADDRESS	GRANISER GRANIT SERAMİK A.Ş.	
OF THE MANUFACTURER,	OSB.Akhisar/Manisa/TURKEY	
TEL.	+90 236 427 2605	
FAX.	+90 236 427 2555	
MAIL	info@graniser.com.tr	
WEB	www.graniser.com	
4- SYSTEM(S) OF ASSESSMENT AND	3 AND 4	
VERIFICATION OF CONSTANCY OF		
PERFORMANCE (AVCP)		
5- NAME AND IDENTIFICATION NUMBER OF NOTIFIED LABORATORY ,AVCP SYSTEM DOCUMEN ISSUED AND DATE OF ISSUE	TURKISH STANDART INSTITUSION, notified laboratory number 1783, performed type testing on determination of release of dangerous substances (lead and cadmium) under system 3 and issued test report no. 149782 on 22 <sup>nd</sup> of May 2012	

## **6-PERFORMANS BEYANLARI**

ESSENTIALCHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class A1	
Release of dangerous substance, for: - Cadmium - Lead	< 0,005 mg/dm <sup>2</sup> < 0,005 mg/dm <sup>2</sup>	TS EN 14411/2013 EN 14411/2012
Breaking strength Thickness ≥ 7,5 mm Thickness < 7,5 mm	>600 N >200 N	
Flexural Tensile Strength Thickness ≥ 7,5 mm Thickness < 7,5 mm	> 12 N/mm <sup>2</sup> > 15 N/mm <sup>2</sup>	
Thermal shock resistance	Pass	
Durability for: - internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

A.Uğur UĞURLU

Manisa 15.06.2018

General Manager