

SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM011712-018

Item No: 500977748






Description:

Chipboard screw torx head with nibs type 17 saw thread waxed blue plated - 4x20

Material: Carbon steel C1022

Certificate No.: [E-30-20650-17](#)

Report No.: [1015-CPR-30-11211/5](#)

	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre)	Head pull-through parameter	Yield moment $I_2 = 1d$	Tensile capacity
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm ²)	(N/mm ²)	(Nmm)	(kN)
										
4.0x20	3.7 - 4.0	2.25 - 2.65	7.64 - 8.0	18.95 - 20.0	Full	3.77	16.93 / 11.11	23.08	3455	6.13
Characteristic density of wood ρ_k (kg/m ³)						350	400	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, (3 - 10) μ m (Service Class 1 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 17 Apr 2019



Hieu Trong Nguyen