



DECLARATION OF PERFORMANCE

YK001/DoP20130107

1. Dry-pressed ceramic tiles with low water absorption $0,5 < E \leq 3 \%$
Group BI b, normative (Annex) H, glazed (GL)
2. Dry-pressed ceramic tiles with low water absorption $0,5 < E \leq 3 \%$
Group BI b, normative (Annex) H, glazed (GL)
Tile size (mm): 97x97x6,5; 100x100x6,5; 75x150x9; 80x330x8; 97x297x7; 197x197x7; 200x200x7;
297x297x7,5; 330x330x8; 400x400x8,5; 425x425x8,5; 450x450x9
3. Intended use:
Ceramic tiles, dry-pressed for internal and external use
4. Name and contact information of manufacturer
Hitit Seramik San. Tic. A.Ş.
Organize Sanayi Bölgesi
PK:43 64100
UŞAK
TÜRKİYE
6. System of assessment and verification of constancy of performance AVCP 4.
7. FPC according AVCP class 4.
9. Relevant clauses

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1FL (CWT)	EN 14411:2012
Release of dangerous substances for: -Cadmium -Lead	TS EN ISO 10545-15 NPD NPD	
Breaking strength Modulus of rupture	thickness $\geq 7,5$ mm 1100N thickness $< 7,5$ mm 700N > 30 N/mm ² TS EN ISO 10545-4	
Bond strength	$> 0,5$ N/mm ² Cementitious adhesive Type C2 / EN 12004	
Durability	Pass	
External use: freeze-thaw resistance	TS EN ISO 10545-12 Pass	

10. Behalf of manufacturer signed: Özkan PEKER, R&D Manager

UŞAK

20.06.2013