

DECLARATION OF PERFORMANCE

PORC001-2013

1. Unique identification code of the product type

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$ type 1

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

**Equipe Cerámicas, S.L.
Ctra. CV-190 km 9.1
12122 Figueroles (CS) Spain**

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory, if relevant

Not relevant

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substances		
- Cadmium	PND	
- Lead	PND	
Breaking strength	> 1300 N	
Slipperiness	PND	
Tactility	PND	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	PND	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:



Rogelio Vila Úbeda, Gerente
Figueroles, 20th May, 2013

