

WetStop Tätband KL

Product information

Article: Tätband KL

Joint sealing tapes for indoor application;

Art.No. 3797 and 3798

Description: Flexible, damp retardent joint sealing tape for flexible

waterproofing underneath tiles or natural stones.

Composition: Substrate; Two outer layers of polypropylene non-

woven, white.

Coating; 100 μ PE-foil, blue

Colour: Blue/white Printing: yes

MaxTotal thickness: ca 0,4 mm

Total weight: ca. 180 gramms / m²

Width ca 120 mm.

Length: 15 m and 30 m

Chemical properties Resistance after storage during += resistant
7 days at room temperature in 0 = weakened
following chemicals -= non resistant

hydorchloric acid, 3,0 % internal +
sulphuric acid, 35 % internal +
citric acid, 100g/ltr internal +
lactic acid, 5 % internal +
potassium hydroxide, 3% /20% internal +/+

potassium hydroxide, 3% /20% internal +/
sodium hypochlorite, 0,3g/ltr internal +
salt water, 20g/ltr sea water salt internal +

Temperature resistance: - 20 / + 90 deg. Celcius

Packaging: 15 m: 10 rolls / box

30 m: 4 rolls / box

storage: Cool and dry, protected against sunlight.

Use within 12 months after receipt.