

# SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Block 16, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province. Vietnam.



## Description

Anchor nail, Round head, ring (double cut), el. Galv, Plating  
Thickness 5µm, 4x40mm

## Dimension

d: 4 mm L: 40 mm

## Nail head

dh: 8 mm

## Material

Carbon steel

## Treatment

Electro galvanized - min. 5 µm








## Certificate No.

E-30-20150-15

## Document No.

KK153 001



	Normal diameter	Total length	Head diameter	Withdrawal parameter (Loading across / along the fibre)	Head pull-through parameter	Yield moment	Tensile capacity
Description	(mm)	(mm)	(mm)	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(Nmm)	(kN)
							
4x40	4	40	8	5.32 / 2.75	24.67	7104	7.92
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )				350	440	-	
Durability (i.e. corrosion protection)				Electro galvanized, min 5µm (Service Class 1 according to EN 1995-1-1)			

**The manufacturer declares for:**

Item No: 501360175.

The products are in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 27-03-2015

Hieu Trong Nguyen