

## Motion detector

# IS 360-3

EAN 4007841006532



## Functional description

The infrared ceiling sensor that satisfies all demands and is really simple to install. Simply genius: sophisticated technology that is installed and configured in just a few steps thanks to a clever installation concept. Thanks to its three pyro sensors, the infrared surface-mounted sensor has an impressive 360° angle of coverage and a range of up to 12 m. The detection zone can be set to any requirement by fitting shrouds. The IS 360-3 is available in black and white.

## Technical specifications

<b>Type</b>	Motion detectors
<b>Dimensions (Ø x H)</b>	121 x 57 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	passive infrared
<b>Application, place</b>	Indoors, outdoors
<b>Type of installation</b>	Surface wiring
<b>Switching zones</b>	972 Schaltzonen
<b>Electronic scalability</b>	No
<b>Mechanical scalability</b>	No
<b>Optimum mounting height</b>	2,8 m
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	90 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	Yes
<b>Reach, tangential</b>	Ø 24 m (452 m²)
<b>Twilight setting TEACH</b>	No
<b>Twilight setting</b>	2 – 1000 lx
<b>Time setting</b>	5 s – 15 min
<b>Switching output 1, resistive</b>	2000 W
<b>Switching output 1, number of LEDs / fluorescent lamps</b>	8 stk.
<b>Constant-lighting control</b>	No
<b>Basic light level function</b>	No
<b>With remote control</b>	No
<b>Interconnection</b>	Yes
<b>IP rating</b>	IP54
<b>Material</b>	Plastic
<b>Ambient temperature</b>	-20 – 50 °C
<b>Colour</b>	white
<b>Colour, RAL</b>	9010
<b>Manufacturer's Warranty</b>	3 years
<b>Version</b>	white