



JOHDINSITEET


Materiaali: Nylon 6.6, muut materiaalit sivulla
 Käyttölämpötila: -40°C ... +85°C
 Värit: Luonnonvalkoinen ja UV-säteilyn kestävä musta, muut värit kysyttäessä.




Tyyppi no.	pituus mm	leveys mm	min. vetolujuus kg	max. johtonipun halkaisija mm	kpl/pakkaus
T18S	80	2,3	8	16	1000
T18R	100	2,5	8	20	200/1000
T18I	144	2,5	8	35	100/1000
T18L	200	2,5	8	50	100/1000
T25R	100	2,5	11	16	1000
T25L	250	2,8	11	65	100
T25LL	330	2,8	11	95	100



T30R	150	3,5	14	35	100/500
T30L	200	3,5	14	50	100/500
T30LL	300	3,5	14	75	100/500
T30L TY	361	3,5	14	101	100
T40R	180	4,0	18	42	100/500
T40L	260	4,0	18	65	100



T50S	155	4,6	23	36	100/500
T50R	200	4,6	23	50	100/500
T50M	250	4,6	23	65	100
T50I	295	4,6	23	81	100
T50L	390	4,6	23	108	100
T50LL	450	4,6	23	132	100



T120S	225	7,6	55	51	100
T120I	295	7,6	55	75	100
T120R	385	7,6	55	108	100
T120M	450	7,6	55	130	100
T120XM	610	7,6	55	170	50
T120L	755	7,6	55	220	50