

DECLARATION OF PERFORMANCE**DK001/DoP20130107**

1. Dry-pressed ceramic tiles with high water absorption E>10%,
Group BIII, normative (Annex) K, glazed (GL)
2. Dry-pressed ceramic tiles with high water absorption E>10%,
Tile size (mm):197x197x7; 200x200x7; 200x250x7; 250x330x7,5; 200x400x8,5; 250x400x8,5; 200x500x9;
330x500x9; 200x600x9,5; 300x600x10
3. Intended use:
Ceramic tiles, dry-pressed for internal walls
4. Name and contact information of manufacturer
Hitit Seramik San. Tic. A.Ş.
Organize Sanayi Bölgesi
PK:43 64100
UŞAK
TÜRKİYE
6. System of assessment and verification of constancy of performance AVCP 4.
7. FPC according AVCP class 4.
9. Relevant clauses

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1FL (CWT)	EN 14411:2012
Release of dangerous substances for: -Cadmium -Lead	TS EN ISO 10545-4 NPD NPD	
Modulus of rupture	thickness <7,5 mm:12N/mm ² thickness ≥7,5 mm:15N/mm ² TS EN ISO 10545-4	
Thermal shock resistance	Pass TS EN ISO 10545-9	
Bond strength	>05N/mm ² Cementitious adhesive Type C2 /EN12004	
Durability	Pass	

10. Behalf of manufacturer signed: Özkan PEKER, R&D Manager

UŞAK

21.06.2013

