



Declaration of Performance



07.1.2021

Document No.: 74187-82304-001

Item No.: 502174187

Description: Collated drywall screw, zinc plated (5 µm)

Diameter: 3,9mm

Length: 51mm

Thread: Coarse thread (H)

Head: Flat trumpet (T)

Point: Sharp (N)

Intended use: Plasterboard to plasterboard/timber

Material: Carbon steel

Cert No.: J-01992-20

Report No.: 32-10432/JZ

AVCP system: 4

Declaration of essential characteristics

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1+A1: 2010
Flexural strength	Pass	EN 14566:2008+A1:2009
Release of dangerous substances	Pass	EN 14566:2008+A1:2009
Protective treatment	Above 48 hours. Service class 1	EN ISO 9227
Withdrawing Force	Minimum value of 450N	EN 14566:2008+A1:2009
Hardness	Minimum case depth 0.05mm, Minimum case hardness HRC 55	EN 14566:2008+A1:2009

The manufacturer declares for:

The product is in accordance with EN 14566:2008+A1:2009 "Mechanical fasteners for gypsum plasterboard systems. Definitions, requirements and test methods."


Simon Vanttinen, Category Manager

KESKO CORPORATION
PO BOX 1, HELSINKI
FI-00016 KESKO

BUSINESS ID FI0109862-8
DOMICILE HELSINKI

TELEPHONE +358 10 53 11
WWW.KESKO.FI