



HIZALTAŞ



DECLARATION OF PERFORMANCE

HPK003/DoP20180703

1. Unique identification code of the product type: Dry-pressed ceramic tiles with low water absorption  $E \leq 0,5$  Group BI a, normative (Annex) G, glazed (GL)

2. Intended use:

Ceramic tiles, dry-pressed for internal and external use

3. Name and contact information of manufacturer

Hitit Seramik San. Tic. A.Ş.  
Organize Sanayi Bölgesi  
PK:43 64100  
UŞAK/TURKEY

4. System of assessment and verification of constancy of performance AVCP 4.

5. Harmonized Standard: EN 14411:2016

6. Declared Performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 FL	EN 14411:2016
Release of dangerous substances for: -Cadmium -Lead	EN ISO 10545-15 NPD NPD	
Breaking strength Modulus of rupture	thickness $\geq 7,5$ mm 1300N thickness $< 7,5$ mm 700N $\geq 35$ N/mm <sup>2</sup> EN ISO 10545-4	
Slipperiness	-	
Durability	EN ISO 10545-12	
Internal use: External use: freeze-thaw resistance	Pass Pass	

The product described in the first item has the performance declared at item 6. The full responsibility for this performance statement only belongs to the manufacturer given in item 3.

Behalf of manufacturer signed:Nihat KARAGÜLER

07.03.2018