


Outdoor light

CAM light

EAN 4007841052997



Functional description

The outdoor CAM light provides more than light and security. Much more. The sensor-switched light with durable aluminium enclosure and high-quality opal glass is the first Wi-Fi-based camera light from STEINEL and is always in touch with you via app. As soon as the 180° infrared motion sensor with a reach of 10 m detects movement, the light is switched ON and you receive a message on your mobile device. The precision-adjustable camera transmits images of your entrance area to your smartphone or tablet via Wi-Fi and provides you with the option of interacting. You can see and hear exactly what is happening outside your front door, and you can communicate from your smartphone or tablet via the built-in intercom unit. As soon as movement is detected, the corresponding images are saved to a micro SD card installed in the light. Thanks to the warm-white light with 3000 K and 781 lm, and an output of 14,3 W, even the darkest shapes are always well illuminated.

Technical specifications

| | |
|--|-------------------------------------|
| Dimensions (L x W x H) | 131 x 78 x 305 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| max | 2,00 m |
| Sensor Technology | passive infrared |
| Output | 14,3 W |
| Interconnection | No |
| Luminous flux | 781 lm |
| Efficiency | 54 lm/W |
| Colour temperature | 3000 K |
| Colour Rendering Index CRI | 80-89 |
| With lamp | Yes, STEINEL LED system |
| Lamp | LED cannot be replaced |
| LED life expectancy (max. °C) | 50000 h |
| Base | without |
| LED cooling system | Passive Thermo Control |
| With motion detector | Yes |
| Detection angle | 180 ° |
| Angle of aperture | 90 ° |
| Sneak-by guard | No |
| Capability of masking out individual segments | No |
| Electronic scalability | Yes |
| Mechanical scalability | No |
| Reach, tangential | passive infrared: r = 10 m (157 m²) |
| Photo-cell controller | Yes |
| Twilight setting | 10 – 10000 lx |
| Time setting | 60 s – 15 min |
| Basic light level function | Yes |
| Soft light start | Yes |
| IP rating | IP44 |
| Protection class | I |
| Ambient temperature | -10 – 40 °C |

<https://www.steinel.de/>

Outdoor light

CAM light

EAN 4007841052997

| | |
|--------------------------------|------------|
| Housing material | Aluminium |
| Cover material | Glass opal |
| Manufacturer's Warranty | 3 years |
| Settings via | Smartphone |
| With remote control | Yes |