

Declaration of Performance, DoP: Homer-19/0338



1. Product type: Homer angle brackets

2. Identification: Kesko item no	Homer's Art#	Size	Material
502109548	J-LAB-130	35x35x130x2.0mm	SS GR340 Z275
502109549	J-LAB-100	35x35x100x2.0mm	SS GR340 Z275
502109553	J-LBJ-160	160x40/85x70x2.0mr	SS GR340 Z275
502114669 J	-ZK-9965WZS/2	90x90x65x2.0mm	SS 304
 5.Authorised representative: N/A 6. System of assessment: 2+ 7. Notified body / Test laboratory: EUROFINS EXPERT SERVICES (performed under system 2+, NB 08 8. For the angle brackets a European EUROFINS EXPERT SERVICES (MANUFACTURING IC DEVELOPMENT OY,Kivimiehentie 4 809 Technical Assessr OY,Kivimiehentie 4	FZONE, JIANGYAN DI FI-02150 ESPOO,FINL nent has been issued: FI-02150 ESPOO,FINL	
issued ETA 13/0338 performed un 9. Declared performance	-		
 Declared performance Characteristic values are calculated a 	-		asic requirements for construction works and
 Declared performance 	nd declared accord	ling to ETA 13/0338. B	asic requirements for construction works an EAD
 Declared performance Characteristic values are calculated a essential characteristics: 	nd declared accord		
Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic	nd declared accord ics ad-carrying capacity	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2	EAD
Declared performance Characteristic values are calculated a <u>essential characteristics</u> : Essential Characteristics Mechanical resistance and stability, Loa	nd declared accord ics ad-carrying capacity	ling to ETA 13/0338. B Performance	EAD ETAG 015 EN 10346
Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1	EAD ETAG 015 EN 10346 EN 13501-1
Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire Elongation at failure A	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1 ≥ 19 %	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015
Declared performance Characteristic values are calculated a <u>essential characteristics:</u> Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1	EAD ETAG 015 EN 10346 EN 13501-1
b. Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire Elongation at failure A	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1 ≥ 19 % Service Class 1 and 2	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015 EN 1995-1-1
 Declared performance Characteristic values are calculated a sesential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R_{p0,2} Reaction to fire Elongation at failure A Durability Z275 	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 $250N/mm^2$ A1 $\geq 19\%$ Service Class 1 and 2 Performance	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015 EN 1995-1-1 EAD
Declared performance Characteristic values are calculated a ssential characteristics: Essential Characteristi Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire Elongation at failure A Durability Z275 Essential Characteristi Mechanical resistance and stability, Loa	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275 A ₈₀ ics ad-carrying capacity	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1 \geq 19 % Service Class 1 and 2 Performance ETA 13/0338 Annex 2	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015 EN 1995-1-1 EAD ETAG 015
Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire Elongation at failure A Durability Z275 Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275 A ₈₀ ics ad-carrying capacity	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 $250N/mm^2$ A1 $\geq 19\%$ Service Class 1 and 2 Performance ETA 13/0338 Annex 2 $230N/mm^2$	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015 EN 1995-1-1 EAD ETAG 015 ASTM A240/A240M
Declared performance Characteristic values are calculated a essential characteristics: Essential Characteristic Mechanical resistance and stability, Loa Characteristic yield strength of R _{p0,2} Reaction to fire Elongation at failure A Durability Z275 Essential Characteristic Mechanical resistance and stability, Loa	nd declared accord ics ad-carrying capacity 2 SS GR340 Z275 A ₈₀ ics ad-carrying capacity R _{p0,2} SS304	ding to ETA 13/0338. B Performance ETA 13/0338 Annex 2 250N/mm ² A1 \geq 19 % Service Class 1 and 2 Performance ETA 13/0338 Annex 2	EAD ETAG 015 EN 10346 EN 13501-1 ETAG 015 EN 1995-1-1 EAD ETAG 015

10.Technical Documentation

EC Certificate of FPC: 0809-CPR-1279

The performance of the products identified above is in conformity with the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

