

## Declaration of Performance



13.3.2020

Document No.:

09552-47389-01

Item No.:

502109552 / J-BP-1251010A2

Description:

Hole band

Width (w):

Length (I):

25mm

Thickness (t):

10000mm 1mm

Intended use:

For use in load bearing timber structures

Material:

SS304

Assessment system:

System 2+

Report No.:

EUFI29-19006337-T1

Certificate No.:

0809-CPR-19002886

Harmonized Standard:

EN 14545:2008

Notified body /test laboratory: NB No.:0809/EUROFINS EXPERT SERVICES OY, Kivimiehentie 4,FI-02150 ESPOO,FINLAND

Declaration of Performance of construction product

Intended use:	For use in load bearing timber structures
Minimum specification of parent material:	SS304 acc. to ASTM A240/A240M
Width (w), length (I) and thickness (tp) dimensions in mm	25x10000x1.0
Characteristic yield strength	Characteristic yield strength fy = 230 N/mm2
Minimum elongation after fracture A80	45%
durability:	Steel grade SS304 (service class 3 acc. to EN 1995-1-1)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Mikko Tiesalo, International Category Manager