



Declaration of Performance

07.10.2019

Document No.: 5020775-001

Item No.: 502077557, 502077558, 502077559, 502077570, 502077571, 502077572, 502077573

Description.: Collated drywall screw, zinc plated (5 µm)

Diameter: 3,9mm

Length: 32-41mm

Thread: Coarse thread (H), coarse reverse thread (U), HiLo thread (U), HiLo reverse thread (U)

Head: Flat trumpet (T)

Point: Sharp (N)

Intended use: Plasterboard to plasterboard/timber/metal

Material: Carbon steel

Report No.: TCZJ18112116111

AVCP system: 4

Declaration of essential characteristics

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1+A1: 2010
Flexural strength	Pass	EN 14566:2008+A1:2009
Release of dangerous substances	Pass	EN 14566:2008+A1:2009
Protective treatment	Above 48 hours. Service class 1	EN ISO 9227
Withdrawing Force	Minimum value of 450N	EN 14566:2008+A1:2009
Hardness	Minimum case depth 0.05mm, Minimum case hardness HRC 55	EN 14566:2008+A1:2009

The manufacturer declares for:

The product is in accordance with EN 14566:2008+A1:2009 "Mechanical fasteners for gypsum plasterboard systems. Definitions, requirements and test methods."

Mikko Tiesalo, International Category Manager