



Declaration of Performance



11.2.2021

Document No.: 22626-00626-001

Item No.: 502222626
Description.: Collated drywall screw, zinc plated
Diameter: 3,5 mm
Length: 25 mm
Thread: Fine thread
Head: Double bugle
Point: Self drilling
Intended use: Plasterboard to steel
Material: Carbon steel C1022
Cert No.: J-02003-20
Report No.: 32-10433/JZ

Declaration of essential characteristics

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1+A1: 2010
Flexural strength	Pass	EN 14566:2008+A1:2009
Release of dangerous substances	Pass	EN 14566:2008+A1:2009
Protective treatment	Above 48 hours. Service class 1	EN ISO 9227
Withdrawing Force	Minimum value of 450N	EN 14566:2008+A1:2009
Hardness	Minimum case depth 0.05mm, Minimum case hardness HRC 55	EN 14566:2008+A1:2009

The manufacturer declares for:

The product is in accordance with EN 14566:2008+A1:2009 "Mechanical fasteners for gypsum plasterboard systems. Definitions, requirements and test methods."

Simon Vanttinen, Category Manager

KESKO CORPORATION
PO BOX 1, HELSINKI
FI-00016 KESKO

BUSINESS ID FI0109862-8
DOMICILE HELSINKI

TELEPHONE +358 10 53 11
WWW.KESKO.FI