



Declaration of Performance



10.1.2021

Document No.: 23784-04938-001
Item No.: 502223784
Description: Anchor nail
Diameter: 4,0 mm
Length: 40 mm
Head: Round/Countersunk
Shank: ring
Intended use: Load bearing timber constructions
Material: Stainless steel 316
Assessment system: System 3+
Report No.: 1015-CPR-30-15206/3/JZ
Certificate No.: CPR-J-01950-20
Notified body / test laboratory: Strojírenský zkušební ústav s.p. N.B. 1015

Declaration of Performance of construction product

Essential characteristics	Performance		Density of wood (kg/m ³)	Harmonized technical specification
Head diameter (mm)	7.40-8.0			EN 14592:2008+A1:2012
Cross-sectional area(mm ²)	42.99-50.24			EN 14592:2008+A1:2012
shank diameter (mm)	3.95-4.05			EN 14592:2008+A1:2012
Total length (mm)	38.5-41.5			EN 14592:2008+A1:2012
Length of thread (mm)	20.9-39.1			EN 14592:2008+A1:2012
Length of point (mm)	5.2-9.4			EN 14592:2008+A1:2012
Yield moment (Nmm)	12000			EN 14592:2008+A1:2012
Tensile capacity (kN)	11.99			EN 14592:2008+A1:2012
Head pull-through parameter (N/mm ²)	32.33		350	EN 14592:2008+A1:2012
Withdrawal parameter (N/mm ²)	Perpendicular to the grain	10.95	350	EN 14592:2008+A1:2012
	Parallel to the grain	5.8	350	EN 14592:2008+A1:2012
Durability	Stainless steel AISI 316 (Service Class 3)			EN1995-1-1

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 Timber structures-Dowel-type fasteners-Requirements.

Aleksi Kivinen

Aleksi Kivinen, Category Manager

KESKO CORPORATION
PO BOX 1, HELSINKI
FI-00016 KESKO

BUSINESS ID FI0109862-8
DOMICILE HELSINKI

TELEPHONE +358 10 53 11
WWW.KESKO.FI