



OAK TERRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS

| | |
|--------------------------------|---|
| Article Number | 151N8AEKF4KW240 |
| EAN Code | 7393969044226 |
| Surface treatment | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. |
| Design features | Microbevelled 4-sided, Brushed, Smoked |
| Dimensions | 2420 x 187 x 15 mm |
| Weight per Package (kg) | 22 kg |
| Area per Package (m²) | 2.7 m² |
| Area per pallet (m²) | 122.4 m² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances the natural colour variations and creates a stronger contrast between light and dark.

COLOUR CHANGE

Smoked product - noticable color change over time

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Lively |
| Range | Kährs Original |
| Collection | Lux Collection |
| Resandable | 2-3 times |
| Natural/Stained | Natural |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3.5 mm |
| Core material | Pine/Spruce/Alder |
| Thickness | 15 mm |
| Surface Colour | Brown |
| Installation method | Floating, Glue-down |

TECHNICAL PROPERTIES

| | | |
|-----------------------------------|-------------|-------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.