

EAN: 6414150098765
static.oras.com/1039F-105

Kitchen faucet with high spout and dishwasher valve with ceramic valve 90° rotation for ON/OFF. Spout's swing angle is factory preset at 120° (can be limited to 0° or 60°). There are also in-built limitation options for water temperature and maximum flow-rate. F = with flexible pipes



- Keuken
- Green Building
- Eengreeps, Dishwasher valve
- Wastafelmontage
- Chroom
- Draaibereik beperkende optie
- Mechanische stopkraan voor vaatwasser
- Eengreeps bediend, Hendel met warm-koud-aanduiding
- Temperatuurbegrenzer
- ø 40 mm keramisch binnenwerk voor debiet en temperatuur instelling
- Flexibele aansluitslangen
- 3S-installatie

Technical data

Flow properties


Flow-rate at 300 kPa (with flow controller)	0.061 l/s
Pressure loss 0.2 l/s (with flow reducers)	240 kPa




Technical properties

DN-size (nominal dimension)	DN8
Hot water supply	max. +80°C
Working pressure	50-1000 kPa
Connection size	G3/8
Projection	178 mm
Material	brass


Regulations

EN standard	EN 817
Noise class	I (ISO 3822)





Spare parts



SP1039F

Name	Code
01 Mousseur, M22x1 Chroom	232201
02 Uitloop Chroom	159695V
03 Begrenzer, 60°/0°	159667/10
03 Begrenzer, 60°/0°	159667V
03 Begrenzer, 120°	159670/10
04 Dichting	159499
05 Hendel Chroom	602502V
06 Kap Chroom	602589V
07 Schroefring	158726
08 Binnenwerk	158890
09 Binnenwerk, G1/2	602600V
10 Handle for washing machine valve Chroom	1005697V
11 Wasser	1002371V
12 Verstevigingsplaat, 100x60mm	158825
13 Bevestigingsschroeven, M8x1, L=130	1000780V
14 Bevestigingsset	602610V