

## Motion detector

# sensIQ S

EAN 4007841034955



## Functional description

Handsome addition! The sensIQ S is just as perfect in form and functional diversity as its larger role model. A look that architects like. This designer motion detector was developed specifically for wall mounting though. Being altogether more compact than its big brother, the sensIQ S nestles up against the facade, perfectly harmonising with modern, purist architecture. Its inner values are spectacular too because it comes with the same highly intelligent features and setting options as the sensIQ.

## Technical specifications

Type	Other
Type of accessory	Corner adapter
Dimensions (L x W x H)	114 x 74 x 128 mm
Mains power supply	100 – 240 V , 50 / 60 Hz
Power supply, detail	500 VA max., 120 V
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	1360 Schaltzonen
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, detail	Reichweite von 2 - 20 m in 3 Richtungen (je 100 °) einstellbar
Reach, radial	r = 20 m (1047 m²)
Reach, tangential	r = 20 m (1047 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Switching output 1, resistive	2000 W
Constant-lighting control	No
Basic light level function	No
With remote control	Yes
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
IDs, certificates	VDE

<https://www.steinel-professional.de/>

Motion detector

## sensIQ S

EAN 4007841034955

**Manufacturer's Warranty**

5 years

**Version**

white

Motion detector

## sensIQ S

EAN 4007841034955

**Sensorenerfassungsbereich 1**



Image not found or type unknown