

SLC LED STRIP MONO CV 60 5M 8MM

4,8W 410LM 830 IP20



LED-strip with low wattage; 4,8 W/m. Suitable for visual decorative effects.
Can be used as background light on walls, inside shelves and niches.

Light technic	
Product ID	S10002
Beam angle	120 °, 120
Colour temperature	3000 K, 3000 - 3000 K
Colour rendering index (CRI/Ra)	80
Number of LED`s per meter	60
Type of light source	LED
Efficacy	85.4 lm/W
Lumens pr. meter	410 lm
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	4.8 W/m
Number of nodes per meter	60 LED`s
Colour of light	White
Luminous flux per meter	410 lm/m
Rated life time L70/B10 at 25 °C	100000 Hours
Rated life time L70/B50 at 25 °C	120000 Hours
Rated life time L80/B10 at 25 °C	60000 Hours
Rated life time L80/B50 at 25 °C	75000 Hours
Rated life time L90/B10 at 25 °C	30000 Hours
Rated life time L90/B50 at 25 °C	35000 Hours
Lamp power per foot	1.44 W
Number of nodes per foot	18
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Exterior color	White
Cutting point, every	100 mm
Dimmable	Yes
Dimming range	0-100% %
Input voltage	24 VDC
IP class	IP20
LED-Strip length	5 m



Max length per connection:	5 meter m
Operating temperature	-10°C ~ +45°C °C
Rated power per meter	4.8 W/m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24 - 24 V
Max. system power	24 W
Technology	Constant voltage (CV)
Dimming method	Pulse Width Modulation (PWM)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	100 mm
3M adhesive tape	Yes
Height/depth	2 mm
Height	2 mm
Length	5000 mm, 5000 mm
Width	8 mm, 8 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938055857