

Product Information

Name: Nylon Cable Glands(metric)

◆**Material:** PA66

◆**Threaded entry** □ Metric

◆**Color:** Light grey

◆**Application temperature** □ -40°C-100°C □ the item can also endure 120°C instantly

◆**IP Class:** IP68

◆**Standard** □ IEC698

◆**Certificate(s):** CE

The product is in conformity with the provisions of the following European directive(s): **RoHS, REACH**

◆**Installation method:** Install it directly on the machine board of the same tooth gauge, insert the cable into the through hole of the fixed head from the other end, and then tighten the tightening nut, which saves time and convenience without removing parts.



Data Spec for all Types:

□ □	D1(mm)	D2(mm)	B1(mm)	L1(mm)	L4(mm)	□□□□□□
Item NO.						Cable range □mm□
M16×1.5	16	10.9	9.6	15	15.8	5-10
M20S×1.5	20	14.8	12.5	15	18.4	3-7
M20M×1.5	20	14.8	12.5	15	18.4	6-12
M20L×1.5	20	15.5	14.5	15	19.5	10-14
M25×1.5	25	21	18.4	15	22.3	13-18

Drawing

◆**Product features:** Special design of clamping jaws and clamping ring, large range of clamping cables, strong tensile force and protection of cables, waterproof, dustproof, salt, weak acid, alcohol, oil, grease and general solvent.