



EUROCEL 907 AC

Short description:

Metallized BOPP single sided tape

Product Data

Backing:	0.030 mm metallized BOPP film
Adhesive:	acrylic water based
Total thickness	0.050 mm
Adhesion to steel	7,5 N/25mm
Tensile strength MD	100 N/25mm
Elongation at break	160 %
Temp. Resistance	80 °C

Application

This product is suitable for joining aluminium insulation panels and for conditioning plants

Features	Benefits
Acrylic adhesive	<ul style="list-style-type: none"> ➤ Good adhesion in most applications ➤ Good resistance to ageing ➤ Good resistance to temperature
Metallized Bopp film	<ul style="list-style-type: none"> ➤ Excellent moisture and vapour barrier (< 1g/mq/24 hours) ➤ Resistant in most situations

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
 Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
 E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss