

CE

DECLARATION OF PERFORMANCE NO.

T5-2013

1.-UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

Mosaic of dry pressed pieces ceramic tiles with water absorption $\leq 0,5 \%$

GROUP BIa

TYPE 5

2.-INTENDED USE:

FOR INTERNAL AND EXTERNAL, FLOORINGS AND WALL FINISHES

3.-NAME AND ADDRESS OF THE MANUFACTURER

INTERMATEX GRUPO

Pol. Ind. "El Colador" Calle Asturias, nº8 C.P.12200 Onda (Castellón) España

4.-SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

5

5.-NAME AND IDENTIFICATION NO. OF THE NOTIFIED OR THE TECHNICAL ASSESSMENT BODY, IF RELEVANT:

NOT RELEVANT

6.-DECLARED PERFORMANCE:

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
REACTION TO FIRE	A1fl		EN 14411:2012
EMISSION OF DANGEROUS SUSTANCES: - CADMIUM - LEAD - OTHERS	NPD (No Performance Determined)		
BREAKING RESISTANCE (N)	Thickness> 6,0 mm	NPD	
SLIP RESISTANCE	NPD (No Performance Determined)		
DURABILITY - INTERNAL USES - EXTERNAL USES: Freeze-thaw resistance	PASS PASS		
TACTILE PROPERTIES	NPD (No Performance Determined)		

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Diego Redondo Garrido / Technical General Manager of INTERMATEX GRUPO.

Villarreal, 18th mARCH, 2019.

