SWISSTEC Sourcing Vietnam

Think Sourcing. Think SWISSTEC

swiss tec

18L1-2 Street 3, Vietnam-Singapore Industrial Park Thu Dau Mot City, Binh Duong Province. Vietnam.

Document No.: *KKM051901-080*

502016271

Screw description:

CBS CSK FLAT HD TX25 HALF THRD SST A2/AISI 304 PASSIV. WAX 5X80

Material:

Certificate No.:

CPR-J-00138-21

SST A2

Report No.:

Item No:

1015-CPR-30-15255/15/JZ

	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio Ftor,k/Rtor,k	Withdrawal parameter (Loading across / along the fibre)	Head pull- through parameter	Yield moment I2 = 1d	Tensile capacity
Size	(mm)	(mm)	(mm)	(mm)	(mm)		(N/mm ²)	(N/mm²)	(Nmm)	(kN)
			dh managan		lg lg	Con and			Contraction of the second seco	•
5x80	4.7 - 5.0	2.95 - 3.15	9.64 - 10.0	78.5 - 80.0	46.8 - 59.2	Min 1.3	15.55 / 12.37	22.49	3839.9 (14 Deg)	4.8
Characteristic density of wood $\rho_{\rm k}$ (kg/m ³)						450	390	450	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995- 1-1)				

The manufacturer declares for:

CE

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements (It cannot be used in construction activities)".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 01 Feb 2023



Hieu Trong Nguyen