SWISSTEC Sourcing Vietnam

Think Sourcing. Think SWISSTEC

swiss tec

18L1-2 Street 3, Vietnam-Singapore Industrial Park Thu Dau Mot City, Binh Duong Province. Vietnam.

Document No.: KKM021710-008

Item No: 501082979

Screw description:

CBS CSK FLAT HD TX25 4NIBS COARSE HALF THRD TYP17 SST A2/AISI 304 5X90/40.5

Material	:	SST

Certificate No.:

CPR-J-00138-21

A2

Report No.:

1015-CPR-30-15255/15/JZ

Size	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio Ftor,k/Rtor,k	Withdrawal parameter (Loading across / along the fibre)	through parameter	Yield moment I2 = 1d	Tensile capacity
Size	(mm)	(mm)	(mm)	(mm)	(mm)		(N/mm²)	(N/mm²)	(Nmm)	(kN)
			dh annan		lg g				40'max	
5x90	4.7 - 5.0	2.95 - 3.15	9.64 - 10.0	88.25 - 90.0	39.0 - 42.0	Min 1.3	15.55 / 12.37	22.49	3839.9 (14 Deg)	4.8
Characteri	Characteristic density of wood ρ_{k} (kg/m ³)					450	390	450	-	
Durability (i.e. corrosion protection)					Stainless steel A2 (Service Class 3 acc. To EN 1995- 1-1)					

The manufacturer declares for:

CF

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements (It cannot be used in construction activities)".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 01 Feb 2023



Hieu Trong Nguyen