

SWISSTEC Sourcing Vietnam Joint Stock Company



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-035

Item No: 502016216

Screw description:

CBS PAN HD TX30 HALF THRD WZP CR3 WAX C1022 5UM 6X100

Material: C1022

Certificate No.: [CPR-J-00133-21](#)

Report No.: [1015-CPR-30-15255/10/JZ](#)

Size	Nominal diameter (mm)	Inner thread diameter (mm)	Head diameter (mm)	Total length (mm)	Thread length (mm)	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) (N/mm ²)	Head pull-through parameter (N/mm ²)	Yield moment (Thread / Smooth section) $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
6x100	5.7 - 6.0	3.6 - 3.85	11.6 - 12.0	98.25 - 100.0	58.5 - 61.5	Min 1.5	14.54 / 11.82	26.89	10730.2 / 18461.4 (Thread/ smooth 12 Deg)	11.7
Characteristic density of wood ρ_k (kg/m ³)						450	350	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated, (3 to 10) μ m (Service Class 1 and 2 acc. to EN 1995-1-1) Ruspert (20 to 25) μ m (Service Class 2 acc. to EN 1995-1-1) Dacromet, (20 to 28) μ m (Service Class 3 acc. to EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 01 Feb 2023



Hieu Trong Nguyen