

# SWISSTEC Sourcing Vietnam Joint Stock Company



*Think Sourcing. Think SWISSTEC*

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province, Vietnam.



Document No.: KKM011712-187

Item No: 501927603








Screw description:

CBS CSK FLAT HD TX25 6NIBS SAW HALF THRD TYP17 WZP CR3  
C10B21 5X90

Material: C10B21

Certificate No.: [CPR-J-00891-20](#)

Report No.: [1015-CPR-30-14940/2/JZ](#)

| Size                                                         | Nominal diameter                                                                   | Inner thread diameter                                                              | Head diameter                                                                      | Total length                                                                       | Thread length                                                                      | Torsional ratio<br>$F_{tor,k}/R_{tor,k}$                                                                                                                                         | Withdrawal parameter<br>(Loading across / along the fibre)<br>(N/mm <sup>2</sup> )   | Head pull-through parameter<br>(N/mm <sup>2</sup> )                                  | Yield moment<br>(Thread / Smooth section)<br>$I_2 = 1d$<br>(Nmm)                     | Tensile capacity<br>(kN)                                                             |
|--------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|                                                              | (mm)                                                                               | (mm)                                                                               | (mm)                                                                               | (mm)                                                                               | (mm)                                                                               |                                                                                                                                                                                  |                                                                                      |                                                                                      |                                                                                      |                                                                                      |
|                                                              |  |  |  |  |  |                                                                                                |  |  |  |  |
| 5x90                                                         | 4.7 - 5.0                                                                          | 2.9 - 3.2                                                                          | 9.64 - 10.0                                                                        | 88.25 - 90.0                                                                       | 58.25 - 61.75                                                                      | Min 1.5                                                                                                                                                                          | 17.36 / 12.87                                                                        | 23.98                                                                                | 5551.8 / 8398.9<br>(Thread/<br>smooth<br>14 Deg)                                     | 8.8                                                                                  |
| Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> ) |                                                                                    |                                                                                    |                                                                                    |                                                                                    |                                                                                    | 350                                                                                                                                                                              | 350                                                                                  | 350                                                                                  | -                                                                                    |                                                                                      |
| Durability (i.e. corrosion protection)                       |                                                                                    |                                                                                    |                                                                                    |                                                                                    |                                                                                    | Blue/yellow zinc plated, thickness min. 3 $\mu$ m (Service Class 1 acc. To EN 1995-1-1)<br>dacromat zinc plated, thickness min. 10 $\mu$ m (Service Class 1 acc. To EN 1995-1-1) |                                                                                      |                                                                                      |                                                                                      |                                                                                      |

## The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 01 Feb 2023



Hieu Trong Nguyen