SWISSTEC Sourcing Vietnam

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2, Thu Dau Mot City, Binh Duong Province. Vietnam.

Document No.:KKM051901-149Item No:502016682Screw description:

CBS PAN HD TX20 HALF THRD SST A2/AISI 304 PASSIV. WAX 4X50

SST A2

Material: Certificate No.: Report No.:

<u>CPR-J-00144-21</u>

<u>1015-CPR-30-15255/21/JZ</u>

	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio Ftor,k/Rtor,k	Withdrawal parameter (Loading across / along the fibre)	Head pull- through parameter	Yield moment I2 = 1d	Tensile capacity
Size	(mm)	(mm)	(mm)	(mm)	(mm)		(N/mm²)	(N/mm²)	(Nmm)	(kN)
	d manager		dh annan		lg lg	Con and			40 max	
4x50	3.75 - 4.0	2.3 - 2.6	7.64 - 8.0	48.75 - 50.0	29.25 - 30.75	Min 1.5	16.34 / 12.67	30.75	2006.4 (17 Deg)	2.9
Characteristic density of wood $\rho_{\rm k}$ (kg/m ³)						450	350	350	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995- 1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements (It cannot be used in construction activities)".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 01 Feb 2023



Hieu Trong Nguyen

CE