

**Floorstanding WC rimless combination with cistern
without fixing holes for floor fixation
ø2715.5**



TECHNICAL DATA

Order no.	ø2715.5
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 782 with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 783
Outlet	vertical
Weight	30,0 kg
Accessories excl.	Seat, order no. ø9115.3 Seat and cover, order no. ø9115.0, ø9115.2 Seat and cover with automatic lowering system, order no. ø9115.1
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm
outlet vertical 70 mm
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked
Further options / accessories: Surface refinement LCC, with shut-off valve option 783, WC seat ø9115.3, WC seat and cover, ø9115.0, ø9115.2, WC seat and cover with automatic lowering ø9115.1
Order no. ø2715.5

TECHNICAL DRAWINGS / S 1 : 20

