



Sustainability scan



Rotary Lift-O-Matic, Advance 60 metre with Ground Spike, 50mm diameter, Cover and Peg Bag



Article information

Article number 11 71 45
Article colour Metallic Grey
Article weight 6664 g

Material

CO2 emissions 28.4 kg
Energy used 1 Mj
Air acidification 143 g SO2
Water pollution 6.4 g PO4

Factory

CO2 emissions 3.0 kg
Energy used 52 Mj
Air acidification 16 g SO2
Water pollution 0.7 g PO4
Region Europe
Made in Latvia

Transport

CO2 emissions 1.6 kg
Energy used 19 Mj
Air acidification 1 g SO2
Water pollution 1.0 g PO4
Transport score 2

Use


CO2 emissions - kg
Energy used - Mj
Air acidification - g SO2
Water pollution - g PO4
Region Europe
Warranty period 5 years
Household score 3
RepairScore

Recycle


Multiple reuse 76.67 %
Reuse 12.08 %
Downgrading 3.74 %
Thermal 7.52 %
Landfill -

Materials


	Good renewable/ Recycled %	Material health code
Zinc plated steel	3737.20 g 40.00	C
Aluminium	1317.50 g 50.00	A
Plastics PP	804.88 g -	B
Plastics PVC	257.00 g -	X
Plastics Polyester	241.00 g -	B
Coil coating	114.00 g -	X
Plastics PEVA	110.00 g -	C
Brass	52.00 g 95.00	B
Plastics EVA	19.00 g -	C
Plastics POM	7.00 g -	C
Plastics PA	2.00 g -	C
Stainless steel AISI 301	1.16 g 60.00	B
Stainless steel AISI 304	1.00 g 60.00	B




Recycled/Good
renewable material




Material health



CO2 emission
33.1 kg



Energy used
72 MJ



End of life