

EAN: 6414150079078

www.oras.com/en/products/oras/product/7495



Thermostatic shower faucet. Temperature handle equipped with safety stop at 38°C. Volume handle with EcoFlow control. The faucet includes vacuum breaker, litter filters and non-return valves. Oras Apollo shower set including hand shower, 650 mm shower rail, soap tray and 1500 mm shower hose.

- Shower
- Thermostatic
- Wall mounted
- Chrome
- shower rail, hand shower, shower rail set, shower hose (1500 mm)
- Eco flow

Technical data

Flow properties

Eco-flow at 300 kPa	0.2 l/s
Flow-rate at 300 kPa	0.28 l/s
Pressure loss with flow (0.2 l/s)	155 kPa

Technical properties


Hot water supply	max. +80°C
Working pressure	100 - 1000 kPa
Connection size	G1/2
Installation width	CC150± 3 mm
Material	brass



Regulations

EN standard	EN 1111
Noise class	I (ISO 3822) Oras lab.


Type approvals

STF certificate	STF VTT-RTH-00085-17
-----------------	-----------------------------






Spare parts



SP520

	Code
01	601189V
01	601189V-11
02	601208V
02	601208V-11



SP7460

	Code
01	602430V
02	109898
03	198094/2
03	178375V
04	602431V
05	178796V
06	178780V