

EAN: 6414150086069
www.oras.com/nl/products/oras/product/6664FTX-109



Touchless thermostatic shower panel with a temperature adjustment handle. Electrical connection 12 V via a separate bus transformer (Oras No. 199501 or 199502). The shower is switched on by placing a hand in front of the sensor within the recognition range. Water will flow for as long as the person is standing under the shower. When the user exits the recognition range the water flow will stop automatically. The shower panel is equipped with litter filters, non-return valves and a flow limiter. Flow-rate 9.0 l/min.

The following accessories are sold separately: soap holder (Oras No. 199880) & grab bar (Oras No. 199881).

Fulfills the requirements for efficient use of water in green building.

- Groene gebouwen
- Elektronisch, Inbouwvoeding, Thermostatisch, Green Building
- Wandmontage
- Aluminium/Chroom
- Temperatuurgreep
- Terugslagklep, Vuilfilter(s), Thermostatische temperatuurregeling
- Autofocus sensor, Magneetventiel
- Instellingen zijn aan te passen (met magneet of met magneetsleutel)

Technical data

Flow properties

Flow-rate at 300 kPa (with flow controller)	0.15 l/s
Pressure loss with flow (0.2 l/s)	200 kPa

Technical properties

Hot water supply	max. +70°C
Working pressure	100 - 1000 kPa
Connection size	G3/4
Installation width	CC150 mm
Material	Aluminium

Software settings

Afterflow period	5 s
Max. flow period	5 min
Opening range	0-5 cm

Electronic properties

Electrical Connection	12 V
-----------------------	------

Regulations

EMC Directive	C € 2004/108/EY
EN standard	EN 1111 , EN 15091
Noise class	I (ISO 3822)
Protection class	IP 55



