

FT0280



TECHNICAL INFORMATION

SERIE : TECH
MODEL : IBIZA WHITE
COLOUR : WHITE
FINISH: GLOSS
SIZE: 25,8 x 29,5 cm.
THICKNESS : 6 mm

APLICATIONS:

INDOORS: ONLY WALL

OUTDOORS: ONLY WALL

WET AREAS: YES, ONLY WALL

POOLS: YES (UNDER STABLE PH AND CHLORINE CONDITIONS ACCORDING TO THE MANUFACTURER'S INSTRUCTIONS)



DESCRIPTION

CERAMIC TILE MOSAIC WITH PORCELAIN BASE AND GLOSSY GLAZED FINISH

DUE TO THE REACTIVE/CRACKED GLAZE USED IN THIS ITEM ITS FINAL APPEARANCE MAY DIFFER SLIGHTLY FROM THIS IMAGE

CHARACTERISTICS

TYPOLOGY: GLAZED PORCELAIN AND PRESSED

SIZE : 258 mm x 295 mm x 6,4 mm

ESPECIFICACIONES

NORM	DESCRIPTION	MINIMUM REQUIRED	SPECIFICATION
			INTERMATEX
ISO 10545-2	Length and width	max. 0.6%	< 0.1%
ISO 10545-2	Flatness of surface	max. 0.5%	< 0.2%
ISO 10545-3	Water absorption	max. 0.5%	< 0.1%

INSTALLATION

INSTALLATION IS MADE WITH FLEXIBLE ADHESIVES, CONTAINING SYNTHETIC ADDITIVES FOR NON ABORBENT MATERIAL. ADHESIVE APPLIED WITH PROPER SQUARED NOTCH TROWEL(3-4 mm). ONCE THE MOSAIC SHEET IS LAID DOWN USE A RUBBER TROWEL OR GROUT FLOAT TO PRESS TO FULLY GUARANTEE THE ADHESION.

CLEANING

CLEAN AND SOFT CLOTH AND DOMESTIC SOAP, NEUTRAL

RECOMMENDATIONS

ALWAYS USE PROTECTIVE GLOVES AND ANTI-CRUSHING FOOTWEAR, PREFERABLY STEEL TOE BOOTS

* SEAL FOR WET AREAS AND/OR IN CASE OF GROUTING WITH DARK COLOURS..

STORAGE

PRODUCT SHOULD BE STORED IN A FLAT SURFACE AND IN A SHELTERED AREA AWAY FROM THE RAIN

PACKING

Pzs/ctn	carton per pallet	Kg. Pallet	sqm per pallet
10	99	1,053.0	77.22