


Technical Data Sheet: **FT0281**

TECHNICAL INFORMATION

SERIE : TECH
MODEL : TOKYO WHITE
COLOUR : WHITE
FINISH: GLOSS
SIZE: 29,0 cm x 30,0m
THICKNESS : 6 mm

USOS :
INTERIOR : FLOOR AND WALL
EXTERIOR : YES
ZONAS HÚMEDAS: YES
PISCINA: YES



DESCRIPTION

CERAMIC TILE MOSAIC WITH PORCELAIN BASE AND GLOSSY GLAZED FINISH

CHARACTERISTICS

TYPOLOGY: GLAZED PORCELAIN AND PRESSED
SIZE : 290mm x 300 mm x 6,3 mm
IT HAS VIRTUALLY A ZERO POROSITY SURFACE, HAS A HIGH RESISTANCE TO ADVERSE WEATHER FACTORS, ESPECIALLY TO FROST. ALL THIS FORMING A MASS OF SOLID AND COMPACT CLAY DOUGH MATERIAL FIRED AT A TEMPERATURE OF 1210 DEGREES CELSIUS.

ESPECIFICACIONES

NORM	DESCRIPTION	VIMUM REQUIRED	SPECIFICATION INTERMATEX
ISO 10545-2	Longitud y Anchura	max. 0.6%	< 0.1%
ISO 10545-2	Planitud de Superficie	max. 0.5%	< 0.2%
ISO 10545-3	Absorción de Agua	max. 0.5%	< 0.1%

INSTALLATION

INSTALLATION IS MADE WITH FLEXIBLE ADHESIVES, CONTAINING SYNTHETIC ADDITIVES FOR NON ABORBENT MATERIAL. ADHESIVE APPLIED WITH PROPER SQUARED NOTCH TROWEL(3-4 mm). ONCE THE MOSAIC SHEET IS LAID DOWN USE A RUBBER TROWEL OR GROUT FLOAT TO PRESS TO FULLY GUARANTEE THE ADHESION.

CLEANING

CLEAN AND SOFT CLOTH AND DOMESTIC SOAP, NEUTRAL

RECOMMENDATIONS

ALWAYS USE PROTECTIVE GLOVES AND ANTI-CRUSHING FOOTWEAR, PREFERABLY STEEL TOE BOOTS
* SEAL FOR WET AREAS AND/OR IN CASE OF GROUTING WITH DARK COLOURS..

STORAGE

PRODUCT SHOULD BE STORED IN A FLAT SURFACE AND IN A SHELTERED AREA AWAY FROM THE RAIN

PACKING

Pcs/ctn	ctns/pallet	Weight/ Pallet (kg.)
10	108	921.0
		74.41