


## TECHNICAL DATA SHEET

### SERIE TECH OCTOGON WHITE 29,4 x 29,4 cm



#### DESCRIPTION

CERAMIC TILE MOSAIC WITH PORCELAIN BASE AND MATT GLAZED FINISH

#### CHARACTERISTICS

TYPOLOGY: GLAZED PORCELAIN AND PRESSED  
SIZE: 294mm x 294 mm x 6 mm - CHIP SIZE :56 mm Y 22 mm  
IT HAS VIRTUALLY A ZERO POROSITY SURFACE, HAS A HIGH RESISTANCE TO ADVERSE WEATHER FACTORS, ESPECIALLY TO FROST. ALL THIS FORMING A MASS OF SOLID AND COMPACT CLAY DOUGH MATERIAL FIRED AT A TEMPERATURE OF 1250 DEGREES CELSIUS.

#### SPECIFICATIONS

NORM	DESCRIPTION	MINIMUM REQUIRED	SPECIFICATION INTERMATEX
ISO 10545-2	Length and width	max. 0.6%	< 0.1%
ISO 10545-2	Flatness of surface	max. 0.5%	< 0.2%
ISO 10545-3	Water absorption	max. 0.5%	< 0.1%

#### APPLICATIONS

THIS TYPE OF MESH CAN BE USED LIKE WALL AND FLOOR TILES (MODERATE TRAFFIC)  
SUITABLE FOR WET AREAS (IN CONDITIONS OF PH AND CHLORINE STABLE ACCORDING TO INDICATIONS OF THE MANUFACTURER)

#### INSTALLATION

INSTALLATION IS MADE WITH FLEXIBLE ADHESIVES, CONTAINING SYNTHETIC ADDITIVES FOR NON-ABSORBENT MATERIAL. ADHESIVE APPLIED WITH PROPER SQUARED NOTCH TROWEL (3-4 mm). ONCE THE MOSAIC SHEET IS LAID DOWN USE A RUBBER TROWEL OR GROUT FLOAT TO PRESS TO FULLY GUARANTEE THE ADHESION.

#### CLEANING

CLEAN AND SOFT CLOTHES AND HOME SOAP, NEUTRAL.

#### RECOMMENDATIONS

ALWAYS USE PROTECTIVE GLOVES AND ANTI-CRUSHING FOOTWEAR, PREFERABLY STEEL TOE BOOTS.

#### STORAGE

PRODUCT SHOULD BE STORED IN A FLAT SURFACE AND IN A SHELTERED AREA AWAY FROM THE RAIN.

#### PACKAGING

Pcs/Box	Box/Pallet	Kg/Pallet	m2 / Pallet
10	108	1.100,0	93,96