

The logo for ARAUCOPLY, featuring the brand name in a bold, white, sans-serif font against an orange background.The text 'Ease of Handling and SPEED IN THE INSTALLATION' is displayed in white, with 'SPEED IN THE INSTALLATION' in a larger, bold font, set against an orange background.

[www.arauco.cl](http://www.arauco.cl)

TECHNICAL SPECIFICATION SHEET



## BC T&G and BC Shiplap ARAUCOPLY Half Panel

ARAUCOPLY panels with profiled edges. Easy installation and firme joints. Ideal for roofs, floors and walls structures, and general applications of the industry. Firm and light.

QUALITY | VERSATILITY | WARMTH OF REAL WOOD

The logo for arauco, featuring the brand name in a bold, black, lowercase sans-serif font.

# The Perfect T&G/Shiplap Plywood for Your Project

**SUPERIOR APPEARANCE**  
Produced with pruned logs

**STABLE COMPOSED CORE**  
Minimal core voids

**150 GRIT**  
Smooth finish

**ARAUCOPLY** panels are sourced from sustainable radiata pine plantation forests, and made of pruned logs for fewer knots, cleaner uniform and light colored faces. The half panel sized in 2.440 x 610 mm has both options of edge profiles (T&G or Shiplap), for easier installation firmer joints and ideal for roofs, floors, walls structures, and general applications of the industry.

### Product Features

- 100% Radiata Pine
- Board with options of tongue and groove or shiplap on its sides
- High quality solid face
- Pre-sanded and ready to use
- Humidity content 8%

### Grades Faces

- **B Grade**
  - Sanding quality, grain 150
  - Limited wood patches
  - No more than 8 synthetic repairs
- **C Grade**
  - Sanding quality, grain 100
  - All types of repairs are accepted

### Product Advantages

- Stable composed core with minimum voids
- With T&G or Shiplap edges that allows stronger joint
- Ease of handling and speed in the installation
- Light weight
- Low resin
- Easy to paint and treat

### Applications Structural for:

- Flooring
- Roofing
- Interior Walls
- General industrial applications

B Grade



C Grade

## ARAUCOPLY T&G AND SHIPLAP - TECHNICAL INFORMATION

Product	Thickness	Sizes	Grades	Profile	Sides	Working Width
	mm	mm				mm
T&G-M	12	2.440 x 610	BC		2S - 4S	600
	15	2.440 x 610				600
	18	2.440 x 610				600
	21	2.440 x 610				600
SHIPLAP	9	2.440 x 610	BC		2S	600
	12	2.440 x 610				600
	15	2.440 x 610				600

Notes: For other formats please contact us.

**ARAUCO**  
150 El Golf Ave., 14<sup>th</sup> Floor  
Las Condes, Santiago, Chile  
Phone: (56) 224 617 200

[www.arauco.cl](http://www.arauco.cl)

### CERTIFICATIONS

PS 1-09	JAS
EN 13986	ISO 14001
AS/NZS 2269.0	OHSAS 18001
BS 5268	FSC® (FSC®-119538)