


FLOORING WOOD TO WOOD SCREW 4,2X35MM CARBON STEEL STANDARD TENSILE



42R35MY

APPLICATIONS

Wood-to-wood applications, subfloor


TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Philips 2
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Point type	Type 17 cut point
Point angle	23 °
Screw length	34 - 36 mm
Screw diameter	4.05 - 4.3 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274008677
Package quantity	1000 pieces
Net weight	2 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Material notification on CE label	Non-alloy steel
Protection level in micron	3
Service class	1
Inner threaded diameter	2.63 mm
Threaded/profiled length	20 mm
Characteristic yield moment	3283 Nmm
Characteristic head pull through parameter	16 N/mm ²
Characteristic tensile capacity	4700 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.47 Nm
Characteristic torsional strength	3.47 Nm