



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu

DECLARATION OF PERFORMANCE 42RH35MY (v0)



Name	Flooring wood to wood screw 4,2x35mm
Article number	42RH35MY
GTIN	8715274027814

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad
Intended use	Self-tapping Screws for timber structures
Unique identification code	42RH35MY
DOP No	42RH35MY
Harmonized standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: 42RH35MY		Performance
Characteristic yield moment	$M_{y,k}$	3283 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	12 N/mm ²
Characteristic head pull through parameter	$f_{head,k}$	16 N/mm ²
Characteristic tensile capacity	$f_{tens,k}$	4700 N
Characteristic torsional strength	$f_{tor,k}$	3,47 Nm
Torsional ratio	$f_{tor,k} / R_{tor,k}$	≥ 1,5
Durability against corrosion		Zinc Plated, SC 1, EN 1995-1-1

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 28-10-2024

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Screw diameter	d	4,2 mm
Screw length	L	35 mm
Threaded/profiled length	l_g	23 mm
Inner threaded diameter	d_i	2,63 mm
Reaction to fire		A1