

TECHNICAL FEATURES	
Collection: Room wall	Brand: Marazzi
Size (cm): 20x60	Thickness (mm): 8,5

Compliant with standard EN 14411:2016 annex L group BIII - GL
 Compliant with standard ISO 13006:2018 annex L group BIII - GL

Technical Features	Testing Method	Meas. unit	Average Typical Values	Established limits		
DIMENSIONAL PROPERTIES AND SURFACE QUALITY						
Dimensions				Nominal Length of edge N (cm) 7≤N<15	Nominal Length of edge N (cm) N≥15	
Length and width (*)	ISO 10545-2	(mm) (%)	Complies with the standards	±2% (max 5mm)	±2% (max 5mm) ±2% (max 5mm)	
Length and width (**)						
Not Rectified			Complies with the standards	± 0,75 mm	±0,5 %	±2,0 mm
Rectified				± 0,4 mm	±0,3 %	±1,0 mm
Thickness						
Not Rectified			Complies with the standards	±0,5 mm	±10 %	±0,5 mm
Rectified				±0,5 mm	±10 %	±0,5 mm
Straightness of sides						
Not Rectified			Complies with the standards	±0,5 mm	±0,3 %	±1,5 mm
Rectified				±0,4 mm	±0,3 %	±0,8 mm
Rectangularity						
Not Rectified			Complies with the standards	±0,75 mm	±0,5%	±0,2 mm
Rectified				±0,4 mm	±0,3%	±1,5 mm
Surface Flatness c.c - e.c.						
Not Rectified			Complies with the standards	+0,75 mm -0,50 mm	+0,5 % -0,3 %	+2,0 mm -1,5 mm
Rectified				±0,6 mm	±0,4%	±1,8 mm
Surface Flatness w.						
Not Rectified			Complies with the standards	±0,75 mm	±0,5 %	±2,0 mm
Rectified				±0,6 mm	±0,4%	±1,8 mm
Surface Quality					Complies with the standards	≥95%
Technical Features	Standard Method		Average Declared Value	Requirements		



Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
 T +39 0536 860800 F +39 0536 860644 info@marazzi.it www.marazzi.it

TECHNICAL FEATURES	
Collection: Room wall	Brand: Marazzi
Size (cm): 20x60	Thickness (mm): 8,5

Technical Features	Testing Method	Meas. unit	Average Typical Values	Established limits
PHYSICAL PROPERTIES				
Water absorption	ISO 10545-3	(%)	> 10	Eb>10 (Individual minimum value 9%)
Modulus of rupture	ISO 10545-4	(N/mm ²)	≥ 12	R ≥15 (Thickness < 7,5 mm) R ≥12 (Thickness ≥7,5 mm)
Breaking Strength	ISO 10545-4	(N)	≥ 600	≥600 (Thickness ≥7,5 mm) ≥200 (Thickness < 7,5 mm)
Linear thermal expansion coefficient	ISO 10545-8	(x(10) ⁻⁶ /°C)	≤ 9	Declared value (EN 14411:2016) Test Method available (ISO 13006:2018)
Thermal shock resistance	ISO 10545-9		Complies with the standards	Declared value (EN 14411:2016) **** Test Method available (ISO 13006:2018)
Crazing Resistance	ISO 10545-11		Complies with the standards	Pass according to EN ISO 10545-1 (EN 14411:2016) Required (ISO 13006:2018)
Reaction to fire	-	-	A1	Class A1 or Class A1 FL (EN 14411:2016)
Color resistance to light exposure	DIN 51094		Complies with the standards	No sample must show noticeable colour modifications.

- (1) Whichever is less.
 (2) May not apply to textured surfaces or tiles with uneven back patterns.
 (3) Whichever is less, for tiles up to 24" (610 mm) on any side
 (4) Applies to tiles larger than 24" (610 mm) on any side
 (5) Glazed tiles only.
 (6) When installation subject to freeze/thaw conditions.
 (7) For Level interior spaces expected to be walked upon when wet (see Section 6.2.2.1.10)
 (8) Class V0 tile only



Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
 T +39 0536 860800 F +39 0536 860644 info@marazzi.it www.marazzi.it

TECHNICAL FEATURES

Collection: Room wall	Brand: Marazzi
Size (cm): 20x60	Thickness (mm): 8,5

CHEMICAL PROPERTIES

Resistance to chemicals for household use and swimming pool salts	ISO 10545-13	A	GB Minimum (EN 14411:2016) GB Minimum (ISO 13006:2018)
Resistance to low concentrations of acids and alkalis	ISO 10545-13	LA-LB	Declared value (EN 14411:2016) Test Method available (ISO 13006:2018)
Resistance to high concentrations of acids and alkalis	ISO 10545-13	HA-HB	Declared value (EN 14411:2016) Test Method available (ISO 13006:2018)
Stain resistance	ISO 10545-14	Class 5	Minimum class 3 (EN 14411:2016) Minimum class 3 (ISO 13006:2018)

- * The work size shall be chose, for non-modular tiles, so that the difference between the work size and the nominal size is:
- ** The deviation, in percent, of the average size for each tile (2 or 4 sides) from the work size..
- **** See Table 2 for uses where it is applicable
- c.c. Centre curvature, related to diagonal calculated from the work sizes
- e.c. Edge curvature, related to the corresponding work sizes.
- w. Warpage, related to diagonal calculated from the work sizes.



Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644 info@marazzi.it www.marazzi.it

TECHNICAL FEATURES

Collection: Room wall

Brand: Marazzi

Size (cm): 20x60

Thickness (mm): 8,5

[PAGINA VOLUTAMENTE LASCIATA IN BIANCO]
[PAGE INTENTIONALLY LEFT BLANK]
[PAGINA DEJADA EN BLANCO INTENCIONADAMENTE]
[CETTE PAGE A ETE LAISSEE DELIBEREMENT BLANCHE]
[SEITE WURDE ABSICHTLICH LEER GELASSEN]



Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644 info@marazzi.it www.marazzi.it