

Technical Data

Certeca– Indústrias Cerâmicas, S.A. states that its monoporous, dry pressed ceramic tiles, prepared for interior wall covering, are manufactured in its industrial unit and fulfill the requirements of annex ZA, according to **EN 14411:2016** norm for system 4 in evidence of conformity and accomplish Regulation (EU) N.º 305/2011. The product features – **20x25 USVA Mat** , are shown on the above table:

Technical features		Test method	Prescribed value	Certeca
	Length and width	EN ISO 10545-2	± 0,5%	± 0,2%
	Thickness		± 10%	± 3%
	Straightness		± 0,3%	± 0,15%
	Orthogonality		± 0,5%	± 0,25%
	Flatness – curvature		- 0,3% a + 0,5%	± 0,2%
	Flatness – warpage		± 0,5%	± 0,2%
	Water absorption	EN ISO 10545-3	10% < E < 20%	E < 20%
	Resistance to bending	Modulus of rupture	> 15N/ mm ²	> 16N/mm ²
		Breaking strength	≥ 600N	> 600N
	Thermal shock resistance	EN ISO 10545-9	Required	Guaranteed
	Crazing resistance	EN ISO 10545-11	Required	Guaranteed
	Resistance against acids and alkalis	Low concentrations	EN ISO 10545-13 Declared by the manufacturer	GLA
		High concentration		GHA
	Clean products resistance	EN ISO 10545-13	Min. GB	GA
	Resistance to stains	EN ISO 10545-14	Min. class 3	5