Safety Data Sheet according to (EC) No 1907/2006 as amended

Got2B gotGloss Spray

SDS No. : 812341
V001.1
Revision: 08.02.2024
printing date: 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
Got2B gotGloss Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use:
Hairspray, Aerosol

1.3. Details of the supplier of the safety data sheet
Henkel AG & Co. KGaA
Düsseldorf Germany
Henkelstr. 67
40191 Düsseldorf
Phone: +49 211-797-0

E-mail address of person responsible for Safety Data Sheet:
Henkel Consumer Brands, e-mail: Elisabeth.Poppe@henkel.com

1.4. Emergency telephone number
The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.
Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP):

Aerosol	Category 1

Extremely flammable aerosol.
Pressurized container: May burst if heated.

2.2. Label elements (CLP)

Hazard pictogram:



Signal word:	Danger
Hazard statement:	H222 Extremely flammable aerosol. H229 Pressurized container: May burst if heated.
Precautionary statement: **Prevention**	P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use.
Precautionary statement: **Storage**	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.

2.3. Other hazards

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.1. Substances

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Butane, n- (< 0.1 % butadiene) 106-97-8 203-448-7 01-2119474691-32	>= 50- < 70 %	Press. Gas H280 Flam. Gas 1A, H220		
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5 297-629-8	>= 20- < 25 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226 Aquatic Chronic 4, H413		
Ethanol denatured 64-17-5 200-578-6 01-2119457610-43	>= 1- < 10 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319	Eye Irrit. 2; H319; C >= 50 %	
Isobutane 75-28-5 200-857-2 01-2119485395-27	>= 1- < 10 %	Flam. Gas 1A, H220 Press. Gas Liquef. Gas, H280		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
In case of adverse health effects seek medical advice.
Remove casualty immediately from danger zone. Take off immediately all contaminated clothing.

Inhalation:
Move to fresh air.

Skin contact:
Rinse with water. Take off all clothing contaminated by the product.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse the mouth. Drink 1-2 glasses of water.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:
None known

5.2. Special hazards arising from the substance or mixture

The release of following substances is possible in case of fire:

carbon oxides.
nitrogen oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus.
Wear protective equipment.

Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations.
Collect contaminated fire fighting water separately. It must not enter drains.
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Take great care to avoid inhalation of the aerosol.

6.2. Environmental precautions

Do not allow to enter drainage system, surface or ground water of not diluted product.
Do not dispose of in wastepaper bin or trash-can.

6.3. Methods and material for containment and cleaning up

Dilute small quantities with large amount of water and rinse.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling advice:
No particular measures required.

Fire and explosion protection information:
Take measures to prevent the build-up of electrostatic charges.
Do not spray onto flame or red-hot objects.
Keep away from sources of ignition - no smoking.

Hygiene measures:
Do not eat, drink or smoke while working.
Immediately remove soiled or soaked clothing.
Wash hands before work breaks and after finishing work.
Keep away from food, beverages and animal feed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container protected against moisture.
For aerosols: protect from direct sunshine and temperatures above 50°C.
Store far from foodstuffs.

7.3. Specific end use(s)
Hairspray, Aerosol

SECTION 8: Exposure controls/personal protection

Only relevant for professional/industrial use

8.1. Control parameters
Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Remarks
Butane 106-97-8	1.000	2.400	Exposure limit(s):	4	TRGS 900
Butane 106-97-8			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5	200	380	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Isobutane 75-28-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5	1.000	2.400	Exposure limit(s):	4	TRGS 900

8.2. Exposure controls

Engineering controls:
Ensure good ventilation/suction at the workplace.

Respiratory protection:
When processing in open systems with aerosol formation wear suitable respiratory protection to avoid inhalation of aerosol particles.

Hand protection:
Not needed.

Eye protection:
No special measures required if used properly.

Skin protection:
Not needed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol clear colourless
Odor	floral, musky
Physical state	aerosol
Melting point	Currently under determination
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Not applicable

Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Currently under determination
Viscosity (kinematic)	Currently under determination
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Partially soluble
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	Currently under determination
Density (20 °C (68 °F))	0,634 g/cm3 Density - calculated::245200
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Container pressure (20 °C (68 °F))	2,3 - 2,7 bar
Container pressure (50 °C (122 °F))	4,7 - 5,2 bar

SECTION 10: Stability and reactivity

10.1. Reactivity
None if used for intended purpose.

10.2. Chemical stability
None known.

10.3. Possibility of hazardous reactions
See section reactivity
None known.

10.4. Conditions to avoid
Keep away from sources of ignition and naked flames.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products
None known.

SECTION 11: Toxicological information

General toxicological information:
The present product is a chemical preparation within the meaning of the chemicals act. The following evaluation has been made on the basis of the toxicological data and content by weight of the individual ingredients.
No information exists about acute toxic, irritative or otherwise harmful effects caused by the product.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Ethanol denatured 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Ethanol denatured 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	LC50	> 5,27 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Ethanol denatured 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol denatured 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol denatured 64-17-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobutane 75-28-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobutane 75-28-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	negative			mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isobutane 75-28-5	negative	oral: feed		Drosophila melanogaster	not specified
Isobutane 75-28-5	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobutane 75-28-5	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d 6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	NOAEL > 5.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isobutane 75-28-5	NOAEL 9000 ppm	inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	5,2 mm2/s		not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:
The ecological evaluation of the product is based on data from the raw material and/or comparable substances.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		not specified
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	LC50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanol denatured 64-17-5	LC50	> 12.000 - 16.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		not specified
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanol denatured 64-17-5	EC50	5.012 mg/l	48 h	Ceriodaphnia dubia	other guideline:

Chronic toxicity (aquatic invertebrates):

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		not specified
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	IC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	not readily biodegradable.	aerobic	31,3 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethanol denatured 64-17-5	readily biodegradable	aerobic	80 - 85 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Isobutane 75-28-5	readily biodegradable	aerobic	71,43 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	2,31	20 °C	other (measured)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	6,01		QSAR (Quantitative Structure Activity Relationship)
Isobutane 75-28-5	2,88	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Butane, n- (< 0.1 % butadiene) 106-97-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated 93685-81-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanol denatured 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobutane 75-28-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Consider national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR	
RID	
ADN	
IMDG	
IATA	

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations/information (Germany):

WGK:	WGK 1: slightly hazardous to water (Germany. List of Substances That Are Not Water-Endangering, AwSV of 21 April 2017, UBA, Banz AT, as amended) Classification in conformity with the calculation method
Storage class according to TRGS 510:	2B

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H413 May cause long lasting harmful effects to aquatic life.

Further information:
This information is not related to the use of the product, it is based on our current level of knowledge.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria