

Declaration of Compliance

Date Issued: March 4, 2025

Issued By: Oy Mini-Maid Ab
Fabriksvägen 4
68700 Terjärv, FINLAND

Articles: 111102, Havi Pro strong lautanen 250kpl/15cm
112206, P18 STANDARD 14x50

Materials: Articles are made of virgin fibre paperboard.

Articles comply with below European Regulations:

- Regulation (EC) No 1935/2004 as subsequently amended and supplemented
- Regulation (EC) No 2023/2006 as subsequently amended and supplemented

and following national specific measures:

- D.M. 21 March 1973 as subsequently amended and supplemented
- Décret n°2007-766 du 10 mai 2007 portant application du code de la consommation en ce qui concerne les matériaux et les objets destinés à entrer en contact avec les denrées alimentaires, as subsequently amended and supplemented
- Fiche MCDA n°4 (V02 – 01/01/2019) Aptitude au contact alimentaire des matériaux organiques à base de fibres végétales destinés à entrer en contact avec des denrées alimentaires
- BfR XXXVI. Paper and paperboard in contact with foodstuffs

Conditions of use:

Articles are suitable for contact with dry, moist and fatty foods up to 90°C at the moment of filling, after which the food cools down. Articles are not intended for use in microwave oven or conventional oven.

Dual use substances:

Based on the information from our paperboard suppliers the articles may contain following substances with a quantitative restriction set in Regulation (EC) No 1333/2008 or Regulation (EC) No 1334/2008 with subsequent amendments:

Calcium carbonate (E170)
Sodium nitrate (E251)
Acetic acid (E260)
Sodium acetates (E262)
Citric acid (E330)
Phosphoric acid (E338)
Sodium phosphates (E339)
Potassium phosphates (E340)
Calcium phosphates (E341)
Magnesium phosphates (E343)
Adipic acid (E355)

Calcium stearate (E470a)
Sorbitan monolaurate (E493)
Hydrochloric acid (E507)
Magnesium chloride (E511)
Sulphuric acid (E513)
Sodium sulphate (E514)
Aluminium sulphate (E520)
Sodium hydroxide (E524)
Ammonium hydroxide (E527)
Silicon dioxide (E551)
Magnesium silicate (E553a)
Talc (E553b)
Bentonite (E558)
Polyvinyl alcohol (PVA) (E1203)
Oxidised starch (E1404)
Monostarch phosphate (E1410)
Distarch phosphate (E1412)
Acetylated starch (E1420)
Propane-1, 2-diol (E1520)
Polyethylene glycol (E1521)

Storage:

Recommended storage conditions are 45-55% relative humidity and 19-23°C and not in direct sunshine. We recommend articles to be used within 36 months from the date of production.



Tom Hästbacka
Technical Adviser