

KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801
- Other means of identification:**
- UFI:** E4S6-S7CX-P009-RXAR
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- Relevant uses: antiseptic
For professional and general consumer use.
Uses advised against (Professional users): not defined
- 1.3 Details of the supplier of the safety data sheet:**
- KiiltoClean Oy
Tengströminkatu 6
PL157, 20101 Turku - FINLAND
Phone: +358 (0) 207710400
asiakaspalvelu@kiiltoclean.fi
www.kiiltoclean.fi
- 1.4 Emergency telephone number:** Poison advisory center in Finland: +358 9 471 977

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
- Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
- Danger**
-
- Hazard statements:**
- Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- Precautionary statements:**
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
- 2.3 Other hazards:**
- Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
- Non-applicable
- 3.2 Mixture:**
- Chemical description:** Aqueous solution based on alcohols and surfactants.
- Components:**
- In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KiiltoClean Oy - Erisan Pro Desifoam - 80801 80801



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification		Concentration
CAS: 64-17-5 EC: 200-578-6 Index: Non-applicable REACH: 01-2119457610-43-XXXX	Ethanol⁽¹⁾ Self-classified		65 - <75 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger	
CAS: 67-63-0 EC: 200-661-7 Index: Non-applicable REACH: 01-2119457558-25-XXXX	Propan-2-ol⁽¹⁾ ATP CLP00		5 - <10 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	
CAS: 75-65-0 EC: 200-889-7 Index: Non-applicable REACH: 01-2119444321-51-XXXX	2-methyl-2-propanol⁽¹⁾ ATP ATP01		1 - <5 %
	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Ethanol CAS: 64-17-5 EC: 200-578-6	% (w/w) >=50: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

- CONTINUED ON NEXT PAGE -

KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801



SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KiiltoClean Oy - Erisan Pro Desifoam - 80801 80801



SECTION 7: HANDLING AND STORAGE (continued)

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Other information:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	950 mg/m ³	Non-applicable
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	500 mg/m ³	Non-applicable
2-methyl-2-propanol CAS: 75-65-0 EC: 200-889-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	5,5 mg/kg	Non-applicable
	Inhalation	214 mg/m ³	Non-applicable	2,7 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	87 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	206 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	114 mg/m ³	Non-applicable
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	89 mg/m ³	Non-applicable
2-methyl-2-propanol CAS: 75-65-0 EC: 200-889-7	Oral	Non-applicable	Non-applicable	0,3 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,7 mg/kg	Non-applicable
	Inhalation	159,8 mg/m ³	Non-applicable	0,5 mg/m ³	Non-applicable

PNEC:

Identification					
Ethanol CAS: 64-17-5 EC: 200-578-6	STP	580 mg/L	Fresh water	0,96 mg/L	
	Soil	0,63 mg/kg	Marine water	0,79 mg/L	
	Intermittent	2,75 mg/L	Sediment (Fresh water)	3,6 mg/kg	
	Oral	0,38 g/kg	Sediment (Marine water)	2,9 mg/kg	
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2251 mg/L	Fresh water	140,9 mg/L	
	Soil	28 mg/kg	Marine water	140,9 mg/L	
	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg	
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg	

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KiiltoClean Oy - Erisan Pro Desifoam - 80801 80801



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2-methyl-2-propanol CAS: 75-65-0 EC: 200-889-7	STP	690 mg/L	Fresh water	2 mg/L
	Soil	1 mg/kg	Marine water	0,2 mg/L
	Intermittent	9,33 mg/L	Sediment (Fresh water)	8,04 mg/kg
	Oral	88700 g/kg	Sediment (Marine water)	0,804 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Eye and face protection

Non-applicable

E.- Body protection

Non-applicable

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Alcohol
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	78 °C
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	23907,31 Pa (23,91 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	810 - 910 kg/m ³
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

KiiltoClean Oy - Erisan Pro Desifoam - 80801**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	7
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Highly water-soluble
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	21 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Keep the product away from sources of heat.

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

- CONTINUED ON NEXT PAGE -

**KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801**



SECTION 10: STABILITY AND REACTIVITY (continued)

Other information:

oxidising agents

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

- CONTINUED ON NEXT PAGE -

**KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801****SECTION 11: TOXICOLOGICAL INFORMATION (continued)****Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72,6 mg/L (4 h)	Rat
Ethanol CAS: 64-17-5 EC: 200-578-6	LD50 oral	6200 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	124,7 mg/L (4 h)	Rat
2-methyl-2-propanol CAS: 75-65-0 EC: 200-889-7	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEi)	

11.2 Information on other hazards:**Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:**Acute toxicity:**

Identification	Concentration		Species	Genus
Ethanol CAS: 64-17-5 EC: 200-578-6	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methyl-2-propanol CAS: 75-65-0 EC: 200-889-7	LC50	961 mg/L (96 h)	Pimephales promelas	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		

Chronic toxicity:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KiiltoClean Oy - Erisan Pro Desifoam - 80801 80801



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Ethanol	NOEC	250 mg/L	Danio rerio	Fish
CAS: 64-17-5 EC: 200-578-6	NOEC	2 mg/L	Ceriodaphnia dubia	Crustacean
2-methyl-2-propanol	NOEC	332 mg/L	Clarias Gariepinus	Fish
CAS: 75-65-0 EC: 200-889-7	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Ethanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64-17-5	COD	Non-applicable	Period	14 days
EC: 200-578-6	BOD5/COD	Non-applicable	% Biodegradable	89 %
Propan-2-ol	BOD5	1,19 g O ₂ /g	Concentration	100 mg/L
CAS: 67-63-0	COD	2,23 g O ₂ /g	Period	14 days
EC: 200-661-7	BOD5/COD	0,53	% Biodegradable	86 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Ethanol	BCF	3
CAS: 64-17-5	Pow Log	-0.31
EC: 200-578-6	Potential	Low
Propan-2-ol	BCF	3
CAS: 67-63-0	Pow Log	0.05
EC: 200-661-7	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Ethanol	Koc	1	Henry	4,61E-1 Pa·m ³ /mol
CAS: 64-17-5	Conclusion	Very High	Dry soil	Yes
EC: 200-578-6	Surface tension	2,339E-2 N/m (25 °C)	Moist soil	Yes
Propan-2-ol	Koc	1.5	Henry	8,207E-1 Pa·m ³ /mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
2-methyl-2-propanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 75-65-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-889-7	Surface tension	2,111E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

- CONTINUED ON NEXT PAGE -

KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801



SECTION 12: ECOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 08*	discarded organic chemicals consisting of or containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN1170
14.2 UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Special regulations: 144, 601
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 1 L
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

- CONTINUED ON NEXT PAGE -

**KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801**



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1170
14.2 UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: II
14.5 Marine pollutant: No
14.6 Special precautions for user
Special regulations: 144
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN1170
14.2 UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Ethanol.
Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Ethanol (Product-type 1, 2, 4, 6) ; Propan-2-ol (Product-type 1, 2, 4)
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

- CONTINUED ON NEXT PAGE -

KiiltoClean Oy - Erisan Pro Desifoam - 80801
80801



SECTION 15: REGULATORY INFORMATION (continued)

The product could be affected by sectorial legislation

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -